

- ▶ Very High Sensitivity
- ▶ Very Fast Response with Light and Middle Distillates
- ▶ Sensitive to Heavy Oils and Hydrocarbon Vapors
- ▶ Leak Location on Section Length
- ▶ Re-usable and Pre-connected Cable
- ▶ Suitable for Explosive Area Service
- ▶ Insensitive to Water and Inorganic Pollutants

Description

The TTK digital sense cable FG-ODC+ detects and locates liquid hydrocarbons and certain water-insoluble liquids and their vapors anywhere along its length. The sensor element is optimized for very fast response with light to middle distillates, and is sensitive to heavy oils such as conventional crude oils, dilbit / synbit, as well as to hydrocarbon vapors. The cable is more sensitive than FG-ODC cable.


Thanks to its embedded microchip, each cable has independent digital addressing, enabling multiple leak detections on a panel output. It offers a fast response, is reusable after detection, and remains unaffected by water or inorganic contamination, making it ideal for humid environments.

Key Advantages

- Standard length 9 ft (3 m) sensor sections.
- Microcontroller embedded in each FG-ODC+ sense cable allowing independent digital transmission to the alarm unit.
- Standard length sense cable provided with built-in plug-socket connector.
- Structure of the sense cable comprising a silicon sensing wire, a continuity wire, a communication wire (proprietary bus) and the power supply wires. Protective external PE braid built on the cable.
- Intrinsically safe - can be used in classified areas: Ex ia IIB T4 Ga (IECEx "Zone 0").
- Reliable detection:
 - Sensitive to heavy oils and vapors.
 - Insensitive to water, inorganic pollutants and external loads (pressure).
- Can be reused, provided that heavy hydrocarbon residues are thoroughly cleaned.
- High sensitivity: examples of detection time: **Diesel at 2-5 minutes (*)**, **Gasoline: less than 1 minute (*)**.
- Detects and locates hydrocarbon leaks on the section length.
- The same unit FG-NET can be connected to FG-ODC+ sense cables and mixed with water or acids / bases sense cables at the same time.
- Easy to install and remove: standard FG-ODC+ cables pre-connected with male / female connectors.

Note (*): depending on liquid composition and leak conditions

Cable Structure



Male and Female Connectors

Technical Data

Compatibility	Digital units: FG-NET*, FG-NET-LL, FG-ALS8-OD, FG-ALS4-OD, FG-A-OD Satellite devices: FG-BBOX*, FG-BBOX-LL Sense cables: Compatible with water and acid sense cables on the same panel output via an interface box. [*FG-DOD interface box required for connecting OD range cables/probes to non-OD range panels]
Reusability	Reusable, as long as the cable hasn't been damaged by prolonged immersion in liquid
Sense Cable Material & Nominal Diameter	PE, 0.39 in (10 mm)
Sensor Wires Material & Nominal Diameter	PE, 0,08 in (2 mm)
Sense Cable Weight (Without Connector)	4.04 lbs / 100 ft (6 kg / 100 m)
Minimum Bend Radius	1.97 in or 50 mm
Sense Cable Color	Green braid
Operating Temperature	-22° to 212°F (-30° to 100°C)
Maximum Pressure	3 bar
Maximum Tensile Strength (Incl. Connection)	88 lb (40 kg)
Connector Nominal Diameter	0.63 in (16 mm)
Connector Ingress Protection (IP Rating - DIN/EN/IEC60529)	IP 68
Explosive Area Classification	Ex ia IIB T4 Ga (ATEX "Zone 0")
Direct Burial Capacity	Possible

Identification Codes

FG-ODC+3	Addressable Oil Sense Cable in 9 ft (3m) with Connectors
Accessories:	
FG-CLOD	Leader Cable, on OD Bus 8771
FG-TMOD	Digital End Plug on OD Bus 8771 for FG-OD Cable
FG-NOD 'N'	OD Bus 8771 Neutral Cable 'N' (9, 22, 49, 98 ft) (1, 3, 7, 15, 30 m) with Connectors
CF-OD50	50 Hold-down Clips with Adhesive for Oil Cables
ES-OD	40 Tags for Oil Cable

Certifications



This brochure has been carefully prepared to ensure technical accuracy but is only intended for promotional use. TTK cannot guarantee that the information contained herein contains no errors or omissions, and hence does not accept responsibility related to the use of its equipment. TTK maintain its obligations set forth in the Standard Terms and Conditions of Sale and will not, under any circumstances, assume liability for any incidental damages, indirect or consequential, arising from the sale, resale, use or misuse of this product. The purchaser(s) accept their responsibility as the sole judgment(s) of the adaptability of the product for the intended use.

FG-NET, FG-SYS and TOPSurveillance are trademarks of TTK S.A.S. © TTK 2025

■ **TTK USA Inc.** / 100 S. Broad Street, Suite 730 Philadelphia, PA 19110 / Tel. +1 610 304 2270 / www.ttkusa.com / sales@ttkusa.com

■ **TTK Headquarters** / 19, rue du Général Foy / 75008 Paris / France / T : +33.1.56.76.90.10 / F : +33.1.55.90.62.15 / www.ttk.fr / ventes@ttk.fr